



Item.No	Output(T)	Stroke(mm)	Effective area(cm ²)	Oil Capacity(L)	Height of Product(mm)	Extended height(mm)	Outside Dia(mm)
RC-0550	5	50	4.9	0.0354	121	171	40
RC-1050	10	50	11.3	0.072	96	146	62
RC-2050	20	50	22	0.14	98	148	88
RC-3050	30	50	31.1	0.22	104	154	105
RC-5050	50	50	56.7	0.354	104	154	128
RC-10050	100	50	95	0.66	136	186	175
RC-15050	150	50	162.8	1.056	152	202	207
RC-20050	200	50	224.2	1.402	156	206	237
WRC-10050	100	50	95	0.66	136	186	175

Item.No	Bore Dia(mm)	Principal Dia(mm)	Thread for input oil-port(ZG)	Saddle protrusion form Plgr (mm)	Weight(Kg)
RC-0550	30	25	NPT1/4"	1	
RC-1050	45	38	3/8"-19	2	3
RC-2050	65	53	3/8"-19	2	5
RC-3050	75	68	3/8"-19	2	6.8
RC-5050	95	65	3/8"-19	2	9.8
RC-10050	130	110	3/8"-19	2	23
RC-15050	164	144	3/8"-19	2	
RC-20050	189	169	3/8"-19	2	
WRC-10050	130	110	3/8"-19		24