



Item.No	Output(T)	Stroke(mm)	Effective area(cm <sup>2</sup> )	Oil Capacity(L)	Height of Product(mm)	Extended height(mm)
RMC-051	5	11	4.9	0.0078	43	54
RMC-101	10	11	11.3	0.016	47	58
RMC-201	20	11	22	0.031	52	63
RMC-301	30	12	31.1	0.05	63	75
RMC-501	50	16	56.7	0.113	69	85
RMC-1001	100	16	95	0.211	86	102
RMC-1501	150	18	162.8	0.338	93	111
RMC-2001	200	18	224.2	0.505	100	118

Item.No	Outside Dia (mm)	Bore Dia(mm)	Principal Dia(mm)	Thread for input oil-port(ZG)	Saddle protrusion form Plgr (mm)	Weight(Kg)
RMC-051	51x40	30	25	NPT1/4"	1	
RMC-101	81x56	43	38	3/8"-19	2	1.5
RMC-201	100x77	60	53	3/8"-19	2	2.7
RMC-301	115x95	75	63	3/8"-19	2	4.5
RMC-501	138x115	95	85	3/8"-19	2	7
RMC-1001	185x160	130	110	3/8"-19	2	15.7
RMC-1501	234x200	164	144	3/8"-19	2	
RMC-2001	274x239	189	169	3/8"-19	2	