



Item.No	Output(T)	Stroke(mm)	Effective area(cm ²)	Oil Capacity(L)	Height of Product(mm)	Extended height(mm)	Outside Dia(mm)
RSC-0550	5	50	9	0.0354	133	183	40
RSC-05100	5	100	9	0.0710	183	283	40
RSC-05150	5	150	9	0.107	232	382	40
RSC-1050	10	50	13.8	0.073	139	189	58
RSC-10100	10	100	13.8	0.145	189	289	58
RSC-10150	10	150	13.8	0.220	239	389	58
RSC-2050	20	50	26.4	0.140	157	207	88
RSC-20100	20	100	26.4	0.280	207	307	88
RSC-20150	20	150	26.4	0.420	257	407	88
RSC-3050	30	50	41.8	0.208	157	207	107
RSC-30100	30	100	41.8	0.416	207	307	107
RSC-30150	30	150	41.8	0.624	257	407	107
RSC-30200	30	200	41.8	0.833	307	507	107
RSC-5050	50	50	78.5	0.350	163	213	127
RSC-50100	50	100	78.5	0.700	213	313	127
RSC-50150	50	150	78.5	1.060	263	413	127
RSC-50200	50	200	78.5	1.400	313	513	127
RSC-10050	100	50	103.8	0.660	149	199	177
RSC-100100	100	100	103.8	1.320	249	349	177
RSC-100150	100	150	103.8	2.1	277	427	177
RSC-100200	100	200	103.8	2.65	327	527	177

Item.No	Bore Dia(mm)	Plunger Dia(mm)	Thread for input oil-port(ZG)	Saddle protrusion form Plgr(mm)	Weight(Kg)
RSC-0550	30	25	1/4"-19	13	
RSC-05100	30	25	1/4"-19	13	3
RSC-05150	30	25	1/4"-19	13	3.5
RSC-1050	43	38	3/8"-19	17	4.3
RSC-10100	43	38	3/8"-19	17	5.5
RSC-10150	43	38	3/8"-19	17	9
RSC-2050	65	58	3/8"-19	20	10
RSC-20100	65	58	3/8"-19	20	6.8
RSC-20150	65	58	3/8"-19	20	12.5
RSC-3050	75	68	3/8"-19	20	14.5
RSC-30100	75	68	3/8"-19	20	
RSC-30150	75	68	3/8"-19	20	9.8
RSC-30200	75	68	3/8"-19	20	18
RSC-5050	95	85	3/8"-19	26	22
RSC-50100	95	85	3/8"-19	26	
RSC-50150	95	85	3/8"-19	26	24
RSC-50200	95	85	3/8"-19	26	30
RSC-10050	130	111	3/8"-19	28	
RSC-100100	130	111	3/8"-19	28	
RSC-100150	130	111	3/8"-19	28	
RSC-100200	130	111	3/8"-19	28	